



Otani - EK2000

Application: Passenger Car

Brand: Otani

Pattern: EK2000

Construction: Radial

Country of Origin: Thailand

Details:

- Good handling on wet and dry roads - Optimized tread pattern design to reduce hydroplaning risk, braking distance and ensure good wet-handling performance. "Inside" and "outside" molded on to show correct direction.
- Good comfort and low noise - Variable tread pattern design to reduce the noise and provide good comfort.
- High mileage and low fuel consumption - Optimized tread compound formula to ensure longevity, good grip and lower fuel consumption.
- Endurance – Spiral full-width nylon cap ply for good endurance.

AVAILABLE SIZES

RIM DIA	Size	Item #	Description	Load Index Speed Symbol	Max Load	Max Inflation Pressure	Section Width	Overall DIA	Tread Depth	Uniform Tire Quality Grading		
										Traction	Temp	Treadwear
in					Lbs	Psi	in	in	32nds/in			
14	185/65R14	S053E	86H RATED RIB	86H	1168	44	7.50	23.4	9	A	A	600
15	185/65R15	S053L	88H RATED RIB	88H	1235	44	7.50	24.5	9	A	A	600
15	195/60R15	S180U	88H RATED RIB	88H	1235	44	7.80	24.3	10	A	A	600
15	195/65R15	S181T	91H RATED RIB	91H	1356	44	8.00	25.0	9	A	A	600
15	205/65R15	S193M	94H RATED RIB	94H	1477	44	8.20	25.6	9	A	A	600
15	205/70R15	S195L	96H RATED RIB	96H	1565	44	8.50	26.2	9	A	A	600
15	215/70R15	S198P	98H RATED RIB	98H	1653	44	8.90	26.8	9	A	A	600
16	205/55R16	S191D	91H RATED RIB	91H	1356	44	8.30	24.9	10	A	A	600
16	205/60R16	S191P	92H RATED RIB	92H	1389	44	8.10	25.7	10	A	A	600
16	205/65R16	S194A	95H RATED RIB	95H	1521	44	8.10	26.5	9	A	A	600
16	215/55R16	S196U	93H RATED RIB	93H	1433	44	8.90	25.3	10	A	A	600
16	215/60R16	S198D	95H RATED RIB	95H	1521	44	8.80	26.1	10	A	A	600
16	225/60R16	S201M	98H RATED RIB	98H	1653	44	8.90	26.6	11	A	A	600