



Otani - SA2000

Application: Passenger Car, Light Truck, Rough Terrain

Brand: Otani

Pattern: SA2000

Construction: Radial

Country of Origin: Thailand

AVAILABLE SIZES

RIM DIA	Size	Item #	Description	Load Index Speed Symbol	Max Load	Max Inflation Pressure	Section Width	Overall DIA	Tread Depth	Uniform Tire Quality Grading		
										Traction	Temp	Treadwear
in					Lbs	Psi	in	in	32nds/in			
16	265/70R16	S211C	112S BSW	112S	2469	44	10.90	30.50	15	640	A	A
16	265/75R16	S211Q	116R BSW	116R	2756	44	10.70	31.50	15	640	A	A
17	265/65R-17XL	S210T	116Q BSW									
18	265/60R18	S210H	110S BSW	110S	2337	44	10.60	30.50	15	640	A	A
20	265/50R20XL	S210C	111S BSW	111S XL	2403	50	10.90	30.50	13	640	A	A

RIM DIA	Size	Item #	Description	PR	Load Index Speed Symbol	Max Load Single	Max Load Double	Max Inflation Pressure	Section Width	Overall DIA	Tread Depth
in						Lbs		Psi	in	in	32nds/in
16	LT245/70R16	S147B	113/110S BSW	8	113/110S	2535	2335	65	10.00	29.40	15
16	LT265/70R16	S148C	121/118S BSW	10	121/118S	3195	2910	80	11.00	30.50	15
16	LT265/75R16	S148I	123/120R BSW	10	123/120R	3415	3085	80	10.80	31.50	15
17	LT265/65R17	S148B	120/117S BSW	10	120/117S	3085	2835	80	10.80	30.40	15
18	LT265/60R18	S148A	119/116S BSW	10	119/116S	3000	2755	80	10.70	30.40	15
18	LT285/65R18	S150G	125/112R BSW	10	125/122R	3640	3305	80	11.65	32.50	15
20	LT275/55R20	S148T	115/112S BSW	8	115/112S	2680	2470	65	10.80	31.90	15