

MUD - TERRAIN TIRE



SA4000

Cut Chip Resistance Tread Rubber Compound

Tearing resistance tread rubber compound for aggressive usage conditions.

Excellent Traction with Low Noise

Optimized tread blocks design for excellent traction with low noise.

Open Shoulder Design for On - Off Road Usage

Strong and open shoulder block design to resist tearing and provide excellent traction for off road usage.

Stronger Casing for Aggressive Usage Condition

Reinforced top sidewall with increased rubber thickness to protect critical sidewall failure zone.



Road 20%



Off-Road 80%

SR4000

	Size	Ply Rating	LI/SS	BSW / WL	Max. Load (kg/lbs)		Rim Width	Max. Inflation Pressure
					Single	Dual	(Inch)	(kPa/psi)
20"	33x12.50R20LT*	10	114Q	BSW / WL	1180 / 2600	-	10.00	450 / 65
	33x12.50R20LT*	12	119Q	BSW / WL	1360 / 3000	-	10.00	550 / 80
	35x12.50R20LT*	10	121Q	BSW / WL	1450 / 3195	-	10.00	450 / 65
	35x12.50R20LT	12	125Q	BSW / WL	1650 / 3640	-	10.00	550 / 80

Variation: BSW = Black Sidewall
 WL = White Letter

*POR = Professional Off Road