



OTANI®

DRIVING CONFIDENCE



**TRUCK AND BUS
RADIAL TIRE
CATALOG 2024**

WWW.OTANITIRE.COM



OH-101

OH-102

OH-104

OH-106

OH-107

OH-108

OH-109

OH-110

OH-111

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH	MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		TREAD DEPTH	INFLATED DIMENSION(mm)		
						(inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	(mm)	SECTION WIDTH	OVERALL DIAMETER	
16"	7.00R16LT	12	OH-112	TL	117/116 L	5.50	1285	2810	1250	2700	90	620	13.0	204	777	
			OH-311	TL	117/116 L	5.50	1285	2810	1250	2700	90	620	16.0	204	783	
		14	OH-117	TL	118/114 L	5.50	1320	2910	1180	2600	112	770	11.0	201	774	
	7.50R16LT	14	OH-112	TL	122/118 L	6.00	1500	3305	1320	2910	100	690	13.5	206	808	
			OH-201	TL	122/118 L	6.00	1500	3305	1320	2910	100	690	13.5	210	809	
			OH-208	TL	122/118 L	6.00	1500	3305	1320	2910	100	690	13.5	214	807	
			OH-314	TL	122/118 L	6.00	1500	3305	1320	2910	100	690	13.5	212	807	
		16	OH-112	TL	124/120 L	6.00	1600	3520	1400	3085	116	800	13.5	206	808	
			OH-117	TL	124/120 L	6.00	1600	3520	1400	3085	116	800	11.0	217	800	
			OH-117	TL	129/128 L	6.00	1850	4080	1800	3970	123	850	11.0	218	800	
	18	OH-208	TL	129/128 K	6.00	1850	4080	1800	3970	123	850	13.5	214	807		
		8.25R16LT	16	OH-112	TL	132/130 L	6.50	2000	4410	1900	4190	116	800	14.0	230	858
	OH-117			TL	132/130 L	6.50	2000	4410	1900	4190	116	800	12.5	239	856	
	OH-201			TL	132/130 L	6.50	2000	4410	1900	4190	116	800	13.5	235	858	
	OH-314			TL	132/130 L	6.50	2000	4410	1900	4190	116	800	13.5	230	858	
18	OH-117		TL	134/129 K	6.50	2120	4675	1850	4080	123	850	12.5	239	856		
OH-208	TL	137/132 K	6.50	2300	5070	2000	4410	123	850	13.5	236	858				
ST235/85R16	14	OH-170	TL	132/127M	6.50	2000	4400	1750	3860	110	760	9.0	235	783		
17.5"	9.5R17.5	14	OH-112	TL	129/127 L	6.75	1850	4080	1750	3860	110	760	14.0	232	842	
			OH-117	TL	129/127 L	6.75	1850	4080	1750	3860	110	760	15.0	238	840	
			OH-311	TL	129/127 L	6.75	1850	4080	1750	3860	110	760	14.0	238	844	
		18	OH-112	TL	143/141 J	6.75	2725	6010	2575	5680	125	860	14.0	232	842	
			OH-117	TL	143/141 J	6.75	2725	6010	2575	5680	125	860	15.0	238	840	
	OH-311	TL	143/141 J	6.75	2725	6010	2575	5680	125	860	14.0	238	844			
	215/70R17.5	12	OH-112	TL	126/124 M	6.00	1700	3740	1600	3520	100	700	12.0	210	742	
	215/75R17.5	12	OH-109	TL	126/124 M	6.00	1700	3740	1600	3520	102	700	10.0	210	768	
			OH-112	TL	126/124 M	6.00	1700	3740	1600	3520	102	700	14.0	210	768	
			OH-115	TL	126/124 M	6.00	1700	3740	1600	3520	102	700	12.0	210	769	
			OH-117	TL	126/124 M	6.00	1700	3740	1600	3520	102	700	13.0	210	768	
			OH-207	TL	126/124 M	6.00	1700	3740	1600	3520	102	700	13.0	210	769	
		14	OH-311	TL	128/126 M	6.00	1800	3970	1700	3740	110	760	13.0	210	771	
			16	OH-109	TL	135/133 K	6.00	2180	4805	2060	4540	125	860	10.0	210	768
				OH-112	TL	135/133 K	6.00	2180	4805	2060	4540	125	860	14.0	210	768
OH-115				TL	135/133 K	6.00	2180	4805	2060	4540	125	860	12.0	210	769	
OH-117	TL	135/133 L	6.00	2180	4805	2060	4540	125	860	13.0	210	768				
OH-311	TL	135/133 K	6.00	2180	4805	2060	4540	125	860	13.0	210	771				



OH-112

OH-113

OH-115

OH-117

OH-118

OH-119

OH-120

OH-121

OH-150

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH	MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		TREAD DEPTH	INFLATED DIMENSION(mm)	
						(inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	(mm)	SECTION WIDTH	OVERALL DIAMETER
17.5"	215/75R17.5	18	OH-115	TL	143/141 J	6.00	2725	6010	2575	5680	125	860	12.0	210	769
	225/75R17.5	12	OH-115	TL	129/127 M	6.75	1850	4080	1750	3860	105	725	13.0	228	781
			OH-311	TL	129/127 M	6.75	1850	4080	1750	3860	105	725	15.0	225	786
	225/80R17.5	14	OH-112	TL	123/122 L	6.75	1550	3415	1500	3305	102	700	13.0	224	810
			OH-117	TL	123/122 L	6.75	1550	3415	1500	3305	102	700	12.0	224	804
			OH-311	TL	123/122 L	6.75	1550	3415	1500	3305	102	700	16.0	228	814
			OH-317	TL	123/122 J	6.75	1550	3415	1500	3305	102	700	18.0	226	816
	235/75R17.5	14	OH-115	TL	132/130 M	6.75	2000	4410	1900	4190	112	775	13.0	235	800
			OH-311	TL	132/130 M	6.75	2000	4410	1900	4190	112	775	13.0	235	800
		16	OH-117	TL	135/133M	6.75	2180	4805	2060	4540	125	860	12.2	233	796
			18	OH-115	TL	143/141 J	6.75	2725	6010	2575	5680	125	860	13.0	235
	OH-311	TL		143/141 J	6.75	2725	6010	2575	5680	125	860	13.0	235	800	
245/70R17.5			16												OH-115
OH-322	TL	136/134M		7.50	2240	4940	2120	4675	120	830	13.5	250	789		
			18											OH-115	TL
19.5"	225/70R19.5	14		OH-152	TL	128/126 L	6.75	1800	3970	1700	3750	110	760	13.5	220
			OH-650	TL	128/126 L	6.75	1800	3970	1700	3750	110	760	15.0	220	817
	245/70R19.5	14	OH-152	TL	133/131 L	7.50	2060	4540	1950	4300	110	760	13.5	243	839
			OH-115	TL	136/134 L	7.50	2240	4940	2120	4675	120	830	15.0	250	845
		16	OH-311	TL	136/134 L	7.50	2240	4940	2120	4675	120	830	15.0	250	845
			18	OH-118	TL	141/140 J	7.50	2575	5675	2500	5510	123	850	12.5	249
	OH-311	TL		144/142 J	7.50	2800	6175	2650	5840	130	900	15.0	250	845	
	265/70R19.5	16	OH-120	TL	140/138 M	7.50	2500	5510	2360	5205	110	760	13.0	262	866
			OH-204	TL	140/138 M	7.50	2500	5510	2360	5205	110	760	15.0	260	870
			OH-322	TL	140/138 M	7.50	2500	5510	2360	5205	110	760	14.5	260	870
		18	OH-118	TL	143/141 J	7.50	2725	6010	2575	5680	125	860	14.0	262	869
			OH-204	TL	143/141 J	7.50	2725	6010	2575	5680	125	860	15.0	260	870
OH-204			TL	143/141 K	7.50	2725	6010	2575	5680	125	860	15.0	260	870	
OH-303	TL	143/141 J	7.50	2725	6010	2575	5680	125	860	16.0	260	873			
285/70R19.5	16	OH-120	TL	146/144 M	8.25	3000	6610	2800	6175	130	900	13.0	279	894	
		OH-322	TL	146/144 M	8.25	3000	6610	2800	6175	130	900	14.5	282	892	
305/70R19.5	18	OH-108	TL	150/148 J	8.25	3350	7390	3150	6940	130	900	14.0	281	896	
		OH-120	TL	148/145 M	9.00	3150	6940	2900	6395	123	850	14.3	297	925	
385/55R19.5	18	OH-111	TL	156 J	12.25	4000	8820	-	-	125	860	18.0	393	916	
435/50R19.5	-	OH-111	TL	160 J	14.00	4500	9920	-	-	130	900	12.0	436	927	
445/45R19.5	-	OH-111	TL	160 J	15.00	4500	9920	-	-	130	900	13.5	432	901	



OH-151

OH-152

OH-153

OH-154

OH-155

OH-170

OH-201

OH-202

OH-203

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH	MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		TREAD DEPTH	INFLATED DIMENSION(mm)	
						(inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	(mm)	SECTION WIDTH	OVERALL DIAMETER
20"	7.50R20	14	OH-211	TT	130/128 L	6.00	1900	4190	1800	3970	120	830	12.0	213	934
	8.25R20	16	OH-303	TT	139/137 K	6.50	2430	5355	2300	5070	135	930	16.0	232	980
	9.00R20	14	OH-101	TT	140/137 L	7.00	2500	5510	2300	5070	105	725	15.0	256	1022
	10.00R20	16	OH-101	TT	147/143 L	7.50	3075	6780	2725	6005	116	800	16.0	276	1058
			OH-107	TT	147/143 L	7.50	3075	6780	2725	6005	116	800	15.0	275	1053
			OH-121	TT	147/143 L	7.50	3075	6780	2725	6005	116	800	16.0	285	1058
			OH-201	TT	147/143 L	7.50	3075	6780	2725	6005	116	800	18.0	276	1058
			OH-228	TT	147/143 L	7.50	3075	6780	2725	6005	116	800	17.0	279	1058
			OH-301	TT	147/143 L	7.50	3075	6780	2725	6005	116	800	18.0	277	1060
			OH-303	TT	147/143 L	7.50	3075	6780	2725	6005	116	800	18.0	274	1058
			18	OH-321	TT	149/145 J	7.50	3250	7160	2900	6395	135	930	21.0	272
	OH-403	TT		149/145 G	7.50	3250	7160	2900	6395	135	930	24.5	276	1072	
	11.00R20	16	OH-101	TT	150/146 K	8.00	3350	7390	3000	6610	120	830	16.0	295	1089
			OH-106	TT	150/146 K	8.00	3350	7390	3000	6610	120	830	16.0	295	1089
			OH-117	TT	150/146 K	8.00	3350	7390	3000	6610	120	830	15.0	296	1083
			OH-201	TT	150/146 K	8.00	3350	7390	3000	6610	120	830	16.3	288	1087
			OH-208	TT	150/146 K	8.00	3350	7390	3000	6610	120	830	17.0	284	1089
			OH-301	TT	150/146 K	8.00	3350	7390	3000	6610	120	830	16.0	290	1087
		18	OH-303	TT	150/146 K	8.00	3350	7390	3000	6610	120	830	19.0	288	1093
			OH-117	TT	152/149 K	8.00	3550	7830	3250	7160	135	930	15.0	296	1083
			OH-121	TT	152/149 K	8.00	3550	7830	3250	7160	135	930	16.3	284	1090
			OH-201	TT	152/149 K	8.00	3550	7830	3250	7160	135	930	16.3	288	1087
			OH-208	TT	152/149 K	8.00	3550	7830	3250	7160	135	930	17.0	284	1089
			OH-213	TT	152/149 K	8.00	3550	7830	3250	7160	135	930	18.5	297	1090
	12.00R20	18	OH-201	TT	154/150 K	8.50	3750	8270	3350	7390	125	860	17.0	310	1124
			OH-210	TT	154/150 K	8.50	3750	8270	3350	7390	125	860	14.5	308	1120
OH-213			TT	154/150 K	8.50	3750	8270	3350	7390	125	860	18.5	310	1128	
OH-305			TT	154/150 K	8.50	3750	8270	3350	7390	125	860	18.5	310	1128	
OH-403			TT	154/150 G	8.50	3750	8270	3350	7390	125	860	24.0	313	1137	
20		OH-307	TT	156/153 K	8.50	4000	8820	3650	8050	130	900	21.8	311	1132	
OH-403	TT	156/153 G	8.50	4000	8820	3650	8050	130	900	24.0	313	1137			
22.5"	10R22.5	14	OH-152	TL	141/139 L	7.50	2575	5675	2430	5355	115	790	13.5	256	1020
	11R22.5	14	OH-151	TL	144/142 L	8.25	2800	6175	2650	5840	105	720	10.4	280	1042
		16	OH-101	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	17.0	280	1055



OH-204 OH-205 OH-206 OH-207 OH-208 OH-209 OH-210 OH-211 OH-213

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH	MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		TREAD DEPTH	INFLATED DIMENSION(mm)	
						(inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	(mm)	SECTION WIDTH	OVERALL DIAMETER
22.5"	11R22.5	16	OH-104	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	14.0	280	1050
			OH-107	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	15.0	280	1055
			OH-113	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	15.0	277	1053
			OH-117	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	15.0	280	1053
			OH-118	TL	148/145 L	8.25	3150	6940	2900	6395	125	860	14.0	279	1059
			OH-121	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	16.7	278	1054
			OH-150	TL	146/143 L	8.25	3000	6610	2725	6005	120	830	14.0	277	1052
			OH-153	TL	146/143 L	8.25	3000	6610	2725	6005	120	830	15.0	276	1053
			OH-154	TL	146/143 L	8.25	3000	6610	2725	6005	120	830	14.0	279	1052
			OH-201	TL	148/145 L	8.25	3150	6940	2900	6395	125	860	16.0	280	1055
			OH-205	TL	148/145 L	8.25	3150	6940	2900	6395	125	860	16.0	280	1051
			OH-301	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	19.0	280	1061
			OH-302	TL	148/145 F	8.25	3150	6940	2900	6395	125	860	23.0	280	1067
			OH-303	TL	148/145 L	8.25	3150	6940	2900	6395	125	860	18.0	280	1058
			OH-312	TL	148/145 K	8.25	3150	6940	2900	6395	125	860	21.0	283	1067
			OH-320	TL	148/145 M	8.25	3150	6940	2900	6395	125	860	18.0	283	1058
			OH-350	TL	146/143 L	8.25	3000	6610	2725	6005	120	830	20.0	277	1064
			OH-351	TL	146/143 L	8.25	3000	6610	2725	6005	120	830	20.5	273	1064
			OH-403	TL	146/143 G	8.25	3000	6610	2725	6005	120	830	24.5	280	1071
			12R22.5	16	OH-101	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	16.0
	OH-107	TL			152/148 M	9.00	3550	7830	3150	6940	125	860	16.0	300	1088
	OH-301	TL			152/148 M	9.00	3550	7830	3150	6940	125	860	22.0	309	1100
	OH-101	TL			152/149 K	9.00	3550	7830	3250	7160	125	860	16.0	306	1090
	OH-107	TL			152/149 K	9.00	3550	7830	3250	7160	135	930	16.0	300	1088
	OH-121	TL			152/149 K	9.00	3550	7830	3250	7160	125	860	16.4	309	1089
	OH-209	TL			152/149 K	9.00	3550	7830	3250	7160	125	860	16.5	298	1082
	OH-213	TL			152/149 K	9.00	3550	7830	3250	7160	135	930	18.0	306	1092
	OH-301	TL			152/149 K	9.00	3550	7830	3250	7160	125	860	22.0	309	1100
	OH-305	TL			152/149 K	9.00	3550	7830	3250	7160	135	930	18.0	306	1092
	OH-312	TL			152/149 K	9.00	3550	7830	3250	7160	125	860	23.0	298	1092
	OH-403	TL			154/150 G	9.00	3750	8270	3350	7390	125	860	24.0	298	1105
	13R22.5	18	OH-210	TL	156/150 K	9.75	4000	8820	3350	7390	125	860	18.5	319	1120
			OH-312+	TL	156/150 K	9.75	4000	8820	3350	7390	125	860	22.0	328	1130
			OH-403	TL	156/150 G	9.75	4000	8820	3350	7390	125	860	25.5	319	1140
	255/70R22.5	16	OH-107	TL	140/137 L	7.50	2500	5510	2300	5070	120	830	13.5	255	935
			OH-152	TL	140/137 L	7.50	2500	5510	2300	5070	120	830	11.0	254	931



OH-301

OH-302

OH-303

OH-306

OH-307

OH-311

OH-312

OH-312+

OH-314

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH	MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		TREAD DEPTH	INFLATED DIMENSION(mm)		
						(inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	(mm)	SECTION WIDTH	OVERALL DIAMETER	
22.5"	255/70R22.5	16	OH-350	TL	140/137 L	7.50	2500	5510	2300	5070	120	830	20.0	253	945	
	275/70R22.5	16	OH-107	TL	148/145 M	8.25	3150	6940	2900	6395	130	900	15.0	276	963	
			OH-320	TL	148/145 M	8.25	3150	6940	2900	6395	130	900	18.0	279	969	
		OH-501	TL	150/148 J (152/148 E)	8.25	3350	7390	3150	6940	130	900	17.0	282	967		
	275/80R22.5	16	OH-107	TL	152/148 J	8.25	3550	7830	3150	6940	130	900	15.0	276	963	
			OH-101	TL	149/146 M	8.25	3250	7160	3000	6610	125	860	16.0	271	1021	
	275/80R22.5	16	OH-302	TL	149/146 G	8.25	3250	7160	3000	6610	125	860	20.0	271	1029	
			295/60R22.5	16	OH-107	TL	150/147 K (149/146 L)	9.00	3350	7390	3075	6780	130	900	12.5	287
	OH-311	TL			150/147 K (149/146 L)	9.00	3350	7390	3075	6780	130	900	18.0	287	937	
	OH-320	TL			150/147 K (149/146 L)	9.00	3350	7390	3075	6780	130	900	17.0	288	935	
	295/75R22.5	14	14	OH-150	TL	144/141 L	9.00	2800	6175	2575	5675	110	760	14.0	298	1014
				OH-151	TL	144/141 L	9.00	2800	6175	2575	5675	110	760	10.5	293	1016
				OH-153	TL	144/141 L	9.00	2800	6175	2575	5675	110	760	15.0	295	1024
				OH-154	TL	144/141 L	9.00	2800	6175	2575	5675	110	760	14.0	296	1023
				OH-350	TL	144/141 L	9.00	2800	6175	2575	5675	110	760	20.5	290	1036
				OH-351	TL	144/141 L	9.00	2800	6175	2575	5675	110	760	20.0	288	1035
		16	16	OH-104	TL	148/145 M	9.00	3150	6940	2900	6395	125	860	14.0	286	1024
				OH-301	TL	148/145 M	9.00	3150	6940	2900	6395	125	860	22.0	288	1038
	295/80R22.5	16	16	OH-101	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	17.0	300	1055
				OH-107	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	15.0	300	1050
				OH-201	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	17.0	300	1052
				OH-206	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	17.0	300	1055
				OH-301	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	22.0	300	1066
				OH-302	TL	152/148 F	9.00	3550	7830	3150	6940	125	860	23.0	300	1066
				OH-312	TL	152/148 K	9.00	3550	7830	3150	6940	125	860	21.0	300	1064
				OH-318	TL	152/148 K	9.00	3550	7830	3150	6940	125	860	18.5	300	1056
				OH-320	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	20.0	303	1060
				OH-368	TL	152/148 M	9.00	3550	7830	3150	6940	125	860	20.0	300	1058
		18	18	OH-107	TL	154/150 M	9.00	3750	8270	3350	7390	125	860	15.0	300	1050
				OH-121	TL	154/150 M	9.00	3750	8270	3350	7390	125	860	16.6	299	1053
	315/60R22.5	16	16	OH-201	TL	154/150 J	9.00	3750	8270	3350	7390	125	860	17.0	300	1052
				OH-107	TL	154/148 L	9.75	3750	8270	3150	6940	130	900	12.5	301	948
OH-311				TL	154/148 L	9.75	3750	8270	3150	6940	130	900	18.0	305	960	
OH-320				TL	154/148 L	9.75	3750	8270	3150	6940	130	900	17.0	313	961	
			OH-107	TL	154/150 L	9.00	3750	8270	3350	7390	130	900	15.0	322	1014	



OH-315 OH-317 OH-318 OH-319 OH-320 OH-321 OH-322 OH-350

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH	MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		TREAD DEPTH	INFLATED DIMENSION(mm)	
						(inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	(mm)	SECTION WIDTH	OVERALL DIAMETER
22.5"	315/70R22.5	16	OH-110	TL	154/150 L	9.00	3750	8270	3350	7390	130	900	15.0	314	1015
			OH-301	TL	154/150 L	9.00	3750	8270	3350	7390	130	900	22.0	314	1015
			OH-319	TL	154/150 L	9.00	3750	8270	3350	7390	130	900	16.5	320	1019
		OH-320	TL	154/150 L	9.00	3750	8270	3350	7390	130	900	21.5	319	1030	
		18	OH-107	TL	156/150 L	9.00	4000	8820	3350	7390	130	900	15.0	322	1014
			OH-110	TL	156/150 L	9.00	4000	8820	3350	7390	130	900	15.0	314	1015
	315/80R22.5	20	OH-101	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	17.0	314	1086
			OH-101 SUPER	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	17.0	314	1086
			OH-107	TL	156/150 L (154/150 M)	9.00	4000	8820	3350	7390	125	860	15.0	314	1086
			OH-121	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	17.0	315	1084
			OH-201	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	15.0	314	1084
			OH-209	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	15.4	318	1082
			OH-301	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	22.0	314	1095
			OH-301	TL	160/157 L	9.00	4535	10000	4125	9090	130	900	22.0	314	1095
			OH-312+	TL	156/150 K	9.00	4000	8820	3350	7390	125	860	22.0	314	1095
			OH-315	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	22.0	324	1090
			OH-319	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	16.5	316	1084
			OH-320	TL	156/150 L	9.00	4000	8820	3350	7390	125	860	21.5	315	1095
			OH-402	TL	156/150 K	9.00	4000	8820	3350	7390	125	860	21.0	314	1095
			OH-107	TL	158/150 L	9.00	4250	9370	3350	7390	130	900	15.0	314	1086
	355/50R22.5	18	OH-108	TL	156 K	11.75	4000	8820	-	-	130	900	13.5	260	933
	385/55R22.5	20	OH-108	TL	160 K	12.25	4500	9920	-	-	130	900	13.0	386	996
	385/65R22.5	20	OH-102	TL	160 K(158 L)	11.75	4500	9920	-	-	130	900	15.0	380	1074
			OH-108	TL	160 K	11.75	4500	9920	-	-	130	900	14.5	388	1078
			OH-119	TL	160 K(158 L)	11.75	4500	9920	-	-	130	900	15.0	387	1070
			OH-203	TL	160 K(158 L)	11.75	4500	9920	-	-	130	900	16.0	380	1074
		OH-108	TL	164 K	11.75	5000	11025	-	-	130	900	14.5	388	1078	
	22	OH-119	TL	164 K XL	11.75	5000	11000	-	-	130	900	15.0	387	1070	
425/65R22.5	20	OH-306	TL	165 K	13.00	5150	11400	-	-	120	830	18.0	426	1130	
445/65R22.5	20	OH-306	TL	169 K	13.00	5800	12800	-	-	130	900	16.5	439	1158	
24"	12.00R24	20	OH-202	TT	160/156 K	8.50	4500	9920	4000	8820	125	860	14.0	310	1214
	325/95R24	22	OH-201	TL	162/160 K	9.00	4750	10500	4500	9920	125	860	19.0	312	1229
			OH-401	TL	162/160 F	9.00	4750	10500	4500	9920	125	860	28.0	312	1235
OH-404	TL	162/160 F	9.00	4750	10500	4500	9920	125	860	31.0	313	1230			
24.5"	11R24.5	16	OH-150	TL	149/146 L	8.25	3250	7160	3000	6610	120	830	14.0	280	1104
			OH-153	TL	149/146 L	8.25	3250	7160	3000	6610	120	830	15.0	287	1102



OH-351

OH-368

OH-401

OH-402

OH-403

OH-404

OH-501

OH-650

RIM DIAMETER	TIRE SIZE	PR	PATTERN	TYPE	LOAD INDEX SPEED SYMBOL	STANDARD RIM WIDTH	MAX LOAD SINGLE		MAX LOAD DUAL		RELATIVE PRESSURE		TREAD DEPTH	INFLATED DIMENSION(mm)	
						(inch)	(kg)	(lbs)	(kg)	(lbs)	(psi)	(kPa)	(mm)	SECTION WIDTH	OVERALL DIAMETER
24.5"	11R24.5	16	OH-154	TL	149/146 L	8.25	3250	7160	3000	6610	120	830	14.0	291	1101
			OH-201	TL	149/146 K	8.25	3250	7160	3000	6610	120	830	19.0	289	1113
			OH-350	TL	149/146 L	8.25	3250	7160	3000	6610	120	830	20.0	286	1115
			OH-351	TL	149/146 L	8.25	3250	7160	3000	6610	120	830	20.5	284	1115
			OH-403	TL	149/146 G	8.25	3250	7160	3000	6610	120	830	24.5	281	1123
	285/75R24.5	14	OH-150	TL	144/141 L	8.25	2800	6175	2575	5675	110	760	13.5	282	1053
			OH-153	TL	144/141 L	8.25	2800	6175	2575	5675	110	760	15.0	281	1062
			OH-155	TL	144/141 L	8.25	2800	6175	2575	5675	110	760	14.0	288	1051
			OH-350	TL	144/141 L	8.25	2800	6175	2575	5675	110	760	20.0	285	1051

